



Heat shrinkable tubing adhesive lined - 1.2 m lengths

TA32/TA42 is designed for environmental sealing and electrical insulation of wire splices, terminations and components.

Features and benefits

- Thin wall adhesive-lined heat shrink tubing
- Highly flame retardant
- Outer wall conforms to UL224
- High shrink ratio



TA32 and TA42 are UL224 listed adhesive lined tubing. Available in 3:1 and 4:1 shrink ratio.



Cut lengths available on request. Please contact us!

MATERIAL	Polyolefin, cross-linked (PO-X)
Operating Temperature	-55 °C to +125 °C
Min. Shrink Temperature	+110 °C
Softening Point Adhesive	+110 °C
Longitudinal Change After Shrinkage	-15 % max.
Dielectric Strength	25 kV/mm
Flammability	flame-retardant, UL 224

TA32 - thin wall, 3:1 shrink ratio



Heat Shrinkable Tubing 3:1 with adhesive



TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Length (L)	Colour	Shrink Ratio	Tools	Article-No.
TA32-3/1	3.0	1.0	0.95	1.2 m	Black (BK)	3:1	30;32	318-30300
TA32-4.5/1.5	4.8	1.5	1.10	1.2 m	Black (BK)	3:1	30;32	318-30450
TA32-6/2	6.4	2.0	1.20	1.2 m	Black (BK)	3:1	30;32	318-30600
TA32-9/3	9.5	3.0	1.30	1.2 m	Black (BK)	3:1	30;32	318-30900
TA32-12/4	12.7	4.0	1.40	1.2 m	Black (BK)	3:1	30;32	318-31200
TA32-19/6	19.0	6.0	1.80	1.2 m	Black (BK)	3:1	30;32	318-31900
TA32-24/8	24.0	8.0	2.50	1.2 m	Black (BK)	3:1	30;32	318-32400
TA32-40/13	40.0	13.0	2.50	1.2 m	Black (BK)	3:1	30;32	318-34000

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

Recommended Tools		
	30	32
	H6100	CHG900
	564	563

For more information on toolings please refer to the Application Tooling chapter.



For product specific approvals and specifications please refer to the Appendix.



Add items to your watchlist!
www.HT.click/9-249



Heat shrinkable tubing adhesive lined - 1.2 m lengths

TA42 - thin wall, 4:1 shrink ratio



Heat Shrinkable Tubing 4:1 with adhesive

TA32 and TA42 are UL224 listed adhesive lined tubing. Available in 3:1 and 4:1 shrink ratio.

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Length (L)	Colour	Shrink Ratio	Tools	Article-No.
TA42-4/1	4.0	1.0	1.00	1.2 m	Black (BK)	4:1	30;32	318-40400
TA42-8/2	8.0	2.0	1.20	1.2 m	Black (BK)	4:1	30;32	318-40800
TA42-12/3	12.0	3.0	1.40	1.2 m	Black (BK)	4:1	30;32	318-41200
TA42-16/4	16.0	4.0	1.80	1.2 m	Black (BK)	4:1	30;32	318-41600
TA42-24/6	24.0	6.0	2.20	1.2 m	Black (BK)	4:1	30;32	318-42400
TA42-32/8	32.0	8.0	2.50	1.2 m	Black (BK)	4:1	30;32	318-43200
TA42-52/13	52.0	13.0	2.55	1.2 m	Black (BK)	4:1	30;32	318-45200

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

Recommended Tools		
	30	32
	H6100	CHG900
	564	563

For more information on toolings please refer to the Application Tooling chapter.



For product specific approvals and specifications please refer to the Appendix.



Add items to your watchlist!

www.HT.click/9-250

