



See online  
technical sheet

## / FLASH&GRIP

Composite insulating gloves with arc flash protection



### / Standards

- CE category : Category 3
- EN 60903:2004 Electric protection : Classes 00 à 4
- Category : R, C
- ASTM F2675
- IEC 61482 (electric arc)
- APC Level : APC 2





### / Use

Bicolor composite gloves available in many sizes and different lengths.  
Integrated mechanical protection: no need of leather protector.  
Arc flash rated by a third party notified body: box test and ATPV.  
To work in complete safety without leather gloves.

## / Technical specifications

- Available sizes : 6, 7, 8, 9, 10, 11, 12
- Main color : Red
- Max voltage use : Alternative (V AC)
- APC Level : APC 2
- Coating material : Latex
- Coating finition : Smooth
- Coating material and finition : Latex double layer
- Number of layer : Double Layer
- Electrical gloves cuff characteristic : Not bypassed
- Percentage of product weight made from recycled material (%) : 0

## / Accessories

	Reference	Designation
	RGX-BGT	Insulating storage box for electrician gloves
	RGX-1704/200	Rubber cleaner
	EOS	Pneumatic gloves tester
	RGX-SAC	RGX-SAC

## / Table legend

Complete the reference with the desired size, example : AFG41-0/10 for a pair of gloves class 0 size 10.

Référence	ATPV	Max. operating voltage (V)	Available sizes	Thickness	Length	EN 60903:2004 Electric protection
AFG36-00	26.3 Cal/cm <sup>2</sup>	500 V AC	6, 7, 8, 9, 10, 11, 12	<2.4 mm	360 mm	Class 00
AFG36-0	71.6 Cal/cm <sup>2</sup>	1 000 V AC	6, 7, 8, 9, 10, 11, 12	<2.9 mm	360 mm	Class 0
AFG41-0	71.6 Cal/cm <sup>2</sup>	1 000 V AC	6, 7, 8, 9, 10, 11, 12	<2.9 mm	410 mm	Class 0
AFG36-1	42.2 Cal/cm <sup>2</sup>	7 500 V AC	7, 8, 9, 10, 11, 12	<3.4 mm	360 mm	Class 1
AFG41-1	42.2 Cal/cm <sup>2</sup>	7 500 V AC	7, 8, 9, 10, 11, 12	<3.4 mm	410 mm	Class 1
AFG36-2	74.5 Cal/cm <sup>2</sup>	17 000 V AC	7, 8, 9, 10, 11, 12	<3.9 mm	360 mm	Class 2
AFG41-2	74.5 Cal/cm <sup>2</sup>	17 000 V AC	7, 8, 9, 10, 11, 12	<3.9 mm	410 mm	Class 2
AFG36-3	73.2 Cal/cm <sup>2</sup>	26 500 V AC	8, 9, 10, 11, 12	<4.2 mm	360 mm	Class 3
AFG41-3*	73.2 Cal/cm <sup>2</sup>	26 500 V AC	8, 9, 10, 11, 12	<4.2 mm	410 mm	Class 3
AFG41-4*	87.7 Cal/cm <sup>2</sup>	36 000 V AC	8, 9, 10, 11, 12	<4.8 mm	410 mm	Class 4