



## Sonic One 320 CCS2-CCS2

Sonic One 320 CCS2-CCS2, Compact outdoor ultra-fast charging station, mode 4

Code: V18A00.

- > Cable (m): 4
- > Communications: Ethernet | 2xSIM 4G | Wi-Fi | GPRS | GSM
- > Output type: 150-920 Vcc - 500 A - 320 kW | 150-920 Vcc - 500 A - 320 kW
- > Connector type: CCS Combo 2 (FF) | CCS Combo 2 (FF)
- > Grid type: Three-phase
- > Charge mode: 4
- > No. Sockets: 2

### Description

The **Sonic One 320** is an ultra-fast charging station designed to significantly reduce charging times in short-stay locations, such as service stations or rest areas. With a maximum power of 320 kW (500 A) in Boost mode, it guarantees the delivery of energy without depending on the vehicle's working voltage. Its high power granularity allows dynamically adapting the charge to the specific needs of each vehicle, thus optimising the available power. For example, you can allocate 280 kW to a vehicle with low battery and 40 kW to another vehicle with lower charging requirements, thus maximising the charging point's performance. In addition, the device has been designed so it can be expanded to 400 kW, offering the possibility of adapting it to the growing needs of the market.

In addition to its performance, it offers an excellent user experience thanks to an accessible design conceived for people with reduced mobility, both due to the height of the interactive elements and to its connection system. It features a 32" anti-vandalism touchscreen that can be used as an intuitive interface and advertising medium. It also includes LED indicators for the charger status and the option of integrating a cable management system, which facilitates its use when connected.

This device is compatible with Circutor's dynamic power management system (DLM) and allows regulating the charge without exceeding the contracted power of the installation. It also has an OCPP protocol to integrate it with remote management platforms, the AutoCharge function and dual modem, and it is compatible with various methods of payment, including various types of POS terminals.

The **Sonic One 320** has been designed to function in environments with high operational requirements, combining power, flexibility, accessibility and ease of maintenance. It is a solution prepared to meet the current and future needs of electrical mobility.

### Application

The **Sonic One 320** is designed for situations that require charging electric vehicles in a short time, such as service stations, rest areas on motorways, as well as in settings where ultra-fast charging solutions are desired, such as charging hubs or fleets of heavy-duty vehicles.



## Sonic One 320 CCS2-CCS2

Outdoor ultra-fast charging station

Code: V18A00.

### Specifications

#### AC power supply

|                 |              |
|-----------------|--------------|
| Consumption     | 340kVA       |
| Input intensity | 545 A        |
| Power factor    | > 0.99       |
| Frequency       | 50 / 60 Hz   |
| Type of network | 3P + PE      |
| Nominal voltage | 400 V ~ ±10% |

#### Electrical characteristics

|                           |        |
|---------------------------|--------|
| Max. output intensity (A) | 500 A  |
| Charging mode             | Mode 4 |
| No. of charges            | 2      |
| Efficiency                | 96%    |

#### Mechanical characteristics

|                                  |                        |
|----------------------------------|------------------------|
| Size (mm) width x height x depth | 1000 x 2200 x 800 (mm) |
| Envelope                         | Stainless steel        |
| Thermal management               | Air cooling fans       |
| Noise                            | < 65 dB                |
| Fastening                        | Ground                 |
| Weight (kg)                      | 660                    |

#### Environmental characteristics

|                                          |                |
|------------------------------------------|----------------|
| Protection class                         | IP55 / IK10    |
| Relative humidity (without condensation) | 5 ... 95 %     |
| Storage temperature                      | -40 ... +70 °C |
| Working temperature                      | -30 ... +55 °C |

#### Communication Network

|                        |                                  |
|------------------------|----------------------------------|
| Protocol               | OCPP 1.6J / 2.0 HW Ready         |
| Technology / Interface | Ethernet 10/100 Base TX (TCP/IP) |

#### Standards

|                                       |                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical safety, Maximum height (m) | ≤ 2000                                                                                                                                                                                                                                                                                                                                                |
| Standards                             | IEC 61851-1, IEC 61851-23, IEC 61851-21-2, IEC 61851-24, IEC 62196-1, IEC 62196-2, IEC 62196-3, Compatible with CHAdeMO, Meets the CCS specification, DIN 70121. ISO 15118 ready, Directives: 2014/53/EU, 2014/30/EU, 2014/35/EU, Modem 4G complies with CE/RED, Compliant with RoHS 2011/65/EU-2017/2102, Meter complies with 2014/32/EU, EN 18031-1 |



## Sonic One 320 CCS2-CCS2

Outdoor ultra-fast charging station

Code: V18A00.

### User interface

|                                       |                                                          |
|---------------------------------------|----------------------------------------------------------|
| RFID (Radio-Frequency Identification) | NFC, ISO/IEC 14443A (MIFARE Classic, MIFARE DESFire EV1) |
| LED                                   | RGB color charging indicator                             |
| Display type                          | 32" anti-vandal colour touchscreen                       |

### Features / performance

|                    |                                                                                                                                                                                                                                                                                                                                                                         |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Energy measurement | DC MID counter                                                                                                                                                                                                                                                                                                                                                          |
| Optional           | 4-pole transient overvoltages (IEC 61643-11 Class II)<br><b>Contactless payment system: Ingenico Sefi2000 (Redsys)</b><br><b>Contactless payment system: Payter Apollo</b><br><b>Contactless payment system: PAX IM30</b><br>Compatibility extension RFID Legic: NFC, ISO/IEC 14443A/B, ISO/IEC 15693, ISO/IEC 18092, (Legic Advant, Legic Prime, Sony FelICA, Calypso) |

### Protection

|         |                             |
|---------|-----------------------------|
| Element | Isolation monitoring device |
|---------|-----------------------------|

### Radio communication

|                   |                            |
|-------------------|----------------------------|
| Technology / Type | Dual Modem 4G / GPRS / GSM |
|-------------------|----------------------------|

### Output 1

|                 |                                    |
|-----------------|------------------------------------|
| Maximum current | 500 A                              |
| Maximum power   | 320 kW                             |
| Voltage range   | 150-920 Vcc                        |
| Connector type  | CCS Combo 2 (FF) (Cable length 4m) |
| Network type    | DC                                 |

### Output 2

|                 |                                    |
|-----------------|------------------------------------|
| Maximum current | 500 A                              |
| Maximum power   | 320 KW                             |
| Voltage range   | 150-920 Vcc                        |
| Connector type  | CCS Combo 2 (FF) (Cable length 4m) |
| Network type    | DC                                 |

### Sonic One 320

Outdoor ultra-fast charging station 320 kW

| CODE    | TYPE                       | Output type                                                 | No. Sockets | Connector type                      | Grid type   | Cable (m) | Communications                           | Cable manegement |
|---------|----------------------------|-------------------------------------------------------------|-------------|-------------------------------------|-------------|-----------|------------------------------------------|------------------|
| V18A00. | Sonic One 320 CCS2-CCS2    | 150-920 Vcc - 500 A - 320 kW   150-920 Vcc - 500 A - 320 kW | 2           | CCS Combo 2 (FF)   CCS Combo 2 (FF) | Three-phase | 4         | Ethernet   2xSIM 4G   Wi-Fi   GPRS   GSM |                  |
| V18A02. | Sonic One 320 CCS2-CCS2 5M | 150-920 Vcc - 500 A - 320 kW   150-920 Vcc - 500 A - 320 kW | 2           | CCS Combo 2 (FF)   CCS Combo 2 (FF) | Three-phase | 5.5       | Ethernet   2xSIM 4G   Wi-Fi   GPRS   GSM |                  |



# Sonic One 320 CCS2-CCS2

Outdoor ultra-fast charging station

Code: V18A00.

| CODE    | TYPE                          | Output type                                                 | No. Sockets | Connector type                      | Grid type   | Cable (m) | Communications                           | Cable manegement |
|---------|-------------------------------|-------------------------------------------------------------|-------------|-------------------------------------|-------------|-----------|------------------------------------------|------------------|
| V18A06. | Sonic One 320 CCS2-CCS2 5M-CM | 150-920 Vcc - 500 A - 320 kW   150-920 Vcc - 500 A - 320 kW | 2           | CCS Combo 2 (FF)   CCS Combo 2 (FF) | Three-phase | 5.5       | Ethernet   2xSIM 4G   Wi-Fi   GPRS   GSM | 1                |

32" vandal-proof FHD colour touchscreen. Insulation monitoring device. Integrated MID energy measurement. RFID reader for identification and recharge activation. Data storage, Ethernet communications, Wi-Fi, dual 4G modem communications; OCPP 1.6J/2.0 HW ready communications protocol. Weight: 660 kg. IP55 - IK10 stainless steel enclosure. Dimensions: 1000 x 2200 x 800 mm (without cable). Cable lengths 4 m or 5.5 m (depending on model SONIC ONE xxx ... -xM").



## Sonic One 320 CCS2-CCS2

---

Outdoor ultra-fast charging station

Code: V18A00.

## Dimensions

---



## Sonic One 320 CCS2-CCS2

Outdoor ultra-fast charging station

Code: V18A00.

